

HANDHELD INDOOR AIR QUALITY METER

Measures CO₂, Temperature and Humidity



The Model AQH-20 Handheld Indoor Air Quality Meter reduces the number of instruments a contractor has to carry by measuring carbon dioxide concentration, air temperature, and humidity percentage in one device. A large backlit LCD shows all three parameters simultaneously. This product offers user selectable engineering units, maximum/minimum/average readings, a hold function, and an audible alarm.


FEATURES/BENEFITS

- · All-in-one unit for carbon dioxide, temperature, and humidity
- · Large backlit LCD for visibility in dark areas
- User configurable alarms for audible indication of hazardous conditions

APPLICATIONS

- · Building commissioning
- Green house monitoring

| MODEL CHART | | | | |
|-------------|-----------------------|----------------|---------------------------|--|
| Model | CO ₂ Range | Humidity Range | Temperature Range | |
| AQH-20 | 0 to 2000 PPM | 0.0 to 99.9% | 14 to 140°F (-10 to 60°C) | |



SPECIFICATIONS

Ranges: CO₂: 0 to 2000 PPM; Temperature: 14 to 140°F (-10 to 60°C); Relative

humidity: 0.0 to 99.9% RH.

Accuracy: CO2: ±30 PPM ±5% of reading; Temperature: ±0.9°F (±0.6°C); Humidity:

±3% RH (10 to 90%), ±5% (0.0 to 9.9% or 90 to 99.9%).

Resolution: CO2: 1 PPM; Temperature: 0.1°F (0.1°C); Humidity: 0.1% RH.

Response Time: CO₂: < 30 s; Temperature: < 2 minutes; Humidity: < 10 minutes.

Display: 4 digits for temperature/CO2 and 3 digits for humidity.

CO2 Sensor: Non-dispersive infrared.

Temperature Limits: 32 to 122°F (0 to 50°C). Humidity Limits (Non-Condensing): 0 to 95% RH.

Power Requirements: (4) 1.5 V AA alkaline batteries, included, user replaceable.

Warm Up Time: 30 s. **Weight:** 6.76 oz (200 g).

| ACCESSORIES | | | |
|-------------|---|--|--|
| Model | Description | | |
| TH-CAL | 33% and 75% salt bath calibration standards | | |